

AIRLESS® spray tips



Table of Double Atomization Skill™ AIRLESS® spray Tips 000.30X.XXX

Double insert Skill™ tip allows low AIRLESS® atomizing pressure without tail. The new generation of Skill™ tips deliver a softer spray pattern on edges for a perfect overlapping on flat line and facilitates the settings on flat line machines.

High reliability: Always clean in production for high productivity with excellent atomization

Easy maintenance: This tip is easier to clean because of his dome shape design.

Tip Caliber	Diameter in mm	Diameter in inches	Water Output			Recommended Tip Diaphragm Auto gun ASI 24 & 40	Gun Filter (Mesh)	Pump Filter (Mesh)	Average Spray angle and fan width at gun target distance of 25 cm or 10 inches from substrate												
			Fluid Pressure - bar (psi)						03	05	07	09	11	13	15	17	19	21			
			70 (1000)	140 (2000)	200 (2860)				15°	25°	35°	40°	50°	55°	70°	80°	90°	100°			
			cc/mn	cc/mn	cc/mn				8 cm	10 cm	16 cm	21 cm	24 cm	29 cm	35 cm	40 cm	48 cm	60 cm			
04	0.23	0.009	220	310	370	12	Red (200)	4 (140)			04-07	04-09	04-11	04-13							
06	0.28	0.011	330	465	560					06-05	06-07	06-09	06-11	06-13	06-15						
07	0.30	0.012	390	550	660	15	Blue (140)	6 (85)		07-05	07-07	07-09	07-11	07-13	07-15						
09	0.33	0.013	450	635	760					09-07	09-09	09-11	09-13	09-15	09-17						
12	0.38	0.015	600	850	1015	15	Yellow (100)	8 (70)				12-09	12-11	12-13	12-15	12-17					
14	0.41	0.017	720	1020	1215								14-11	14-13	14-15	14-17	14-19				
18	0.46	0.019	950	1345	1605	20		12 (55)						18-13	18-15	18-17	18-19				
20	0.51	0.020	1060	1500	1790									20-13	20-15	20-17	20-19				

Accessories

Description	Part number
Pack of 10 collars	134.980.002
Pack of 10 collars with integrated screen filter for low caliber #04 and #06	134.980.010